

Smartender Chill®

Crafted in collaboration with Lancer Worldwide, the Smartender Chill brings all the benefits of the original Smartender Automated Cocktail Dispenser, now with added enhancements. This back bar guarantees consistent and accountable cocktail dispensing to any location equipped with a standard US electrical outlet. Moreover, it seamlessly integrates into locations with pre-existing water and soda lines.

Features and Benefits

Effortlessly integrates with existing water, and carbonated systems enhancing your beverage service with ease and efficiency.

Interactive display alerts for low or depleted liquor levels.

Adaptable selection of liquors/mixers, tailored to customer preferences, guaranteeing a superior cocktail experience.

Our innovative, patented pouring nozzle ensures optimal flavors for all ingredients.

Sophisticated drink modifier recognition, compatible with even the most distinctive Point of Sale configurations.

Manage your machine remotely and access reports through the Smartender Ops Service when connected online.

With simultaneous dispensing of liquors and mixers, we achieve an impressive average pour time of just 4 seconds per drink.

Precision liquor dispensing, accurate to within 1/16th of an ounce.

The undercarriage chill unit ensures all alcohol and mixers are kept cold for optimal dispensing.

Technical Specifications

•	
Liquor Capacity	8 distinct liquors, with flexibility to adjust based on customer preferences
Mixer Capacity	8 distinct mixers, with flexibility to adjust based on customer preferences
Electrical	120 VAC, 20 Amp (Smartender) 115 VAC, 2.5 Amps (Hoshizaki)
Safety	Individual ETL Electrical and Sanitation
Dimensions	59.5in L X 29in D X 53.14in H
Weight	450lb Loaded (weight subject to change)
Display	10" Resistive Touch Screen
Connectivity	2.4/5.0 GHz Wireless, LAN





1(866)399-7160 CONTACT@SMARTBARUSA.COM

US & Foreign Patents & Patent Pending Nos.: US8584900, US8651333, US8746507, US9371219, US9776848, US9652756, GB2483129, JP5878467, J/001782, ZL201080003573.X, MX332670, HK1181739, AT2582616, BE2582616, CH2582616, DK2582616, FR2582616, GB2582616, RZ582616, NZ582616, ES2582616, ES2582617, ESS582616, ES2582617, ESS582616, ES2582617, ESS582616, ES2582617, ESS582616, ES2582617, ESS582616, ES2582617, ESS582616, ESS582617, ESS58261